



FLEX

THE INTELLIGENT PORTABLE DEHUMIDIFIER

Easy plug-n-play installation
Same efficiency at all temperatures
Connection for monitoring via external control systems

Technical specifications

FLEX BASIC

Color	Black
Temperature level range (°C)	-10° to +40°C
Relative humidity level range (RH)	10% to 100%
Connection	230V 1-50Hz 10A
Average power	< 400W
Enclosure	IP63
Air flow	400m3/h
Fuse	10A
Dimensions WxHxL	340x650x1060mm
Weight	20kg
Noise	65 dB
Filter standard	G4




A FLEX fixed to the wall with a wall mount

The installation is easy and smooth

The only thing you need is an electrical supply and drainage of the condensed water. All dehumidifiers in the FLEX series are self-regulating on relative humidity and you always have full control over the functions in the display.

Smart monitoring of moisture levels via connection

Equipped with a connection, you can easily follow how the moisture level drops from your computer or mobile phone.

	 FLEX SMART	 FLEX CLOUD	 FLEX INTEGRATE
Color	Black, White	Black, White	Black, White
Adjustable airflow	✓	✓	✓
Dew point control	✓	✓	✓
Control on mold curve	✓	✓	✓
Handle Float	✓	✓	✓
External control with closing relay	✓	✓	✓
Heat support	✓	✓	✓
Temp Guard	✓	✓	✓
WiFi connection	-	✓	✓
Modbus	-	-	✓