



Easy plug-n-play installation
Same efficiency at all temperatures
Connection for monitoring via external control systems







Technical specifications



Color	Black		
Temperature level range	-10° to +40 °C		
Relative humidity level range	10 % to 100 % RH		
Capacity	5 L / 24 h		
Connection	230 V 1-50 Hz 10 A		
Average power	< 400 W		
Enclosure	IP63		
Air flow	400 m3/h		
Fuse	10 A		
Dimensions WxHxL	340x650x1060 mm		
Weight	20 kg		
Noise	65 dB		
Filter standard	G4		



The installation is easy and smooth

The only thing you need is an electrical supply and drainage of the condensed water. All dehumidifiers in the FLEX series are self-regulating on relative humidity and you always have full control over the functions in the display.

Smart monitoring of moisture levels via connection

Equipped with a connection, you can easily follow how the moisture level drops from your computer or mobile phone.

	SMART	CLOUD	INTEGRATE
Color	Black, White	Black, White	Black, White
Adjustable airflow	✓	✓	✓
Dew point control	✓	✓	✓
Control on mold curve	✓	✓	✓
Handle Float	✓	✓	✓
External control with closing relay	✓	✓	✓
Heat support	✓	✓	✓
Temp Guard	✓	✓	✓
WiFi connection	-	✓	✓
Modbus	-	-	✓



