



REX

AIRWATERGREEN

A POWERFUL INDUSTRIAL DEHUMIDIFIER

Halved energy consumption compared to traditional technology

Same efficiency at all temperatures and all moisture levels

Connection for monitoring and control

Easy plug-n-play installation

Technical specifications

Effective dehumidification of large volumes of air

Properties, water facilities and other medium-sized premises above and below ground.

Mobile and simple to install

Remote control via AWG Cloud API and/or offline control via Modbus



**REX
BASIC**



**REX
CLOUD**



**REX
INTEGRATE**

	Black	Black, White	Black, White
Color	Black	Black, White	Black, White
Temperature level range (°C)	0° to +50°C	0° to +50°C	0° to +50°C
Relative humidity level range (RH)	10% to 100%	10% to 100%	10% to 100%
Connection	400V 3-50Hz 16A	400V 3-50Hz 16A	400V 3-50Hz 16A
Average power	< 1600W	< 1600W	< 1600W
Enclosure	IP63	IP63	IP63
Air flow	1000 m ³ /h	1000 m ³ /h	1000 m ³ /h
Fuse	16A	16A	16A
Dimensions WxHxL	750x780x1900mm	750x780x1900mm	750x780x1900mm
Weight	85kg	85kg	85kg
Noise	< 65 dB (A)	< 65 dB (A)	< 65 dB (A)
Filter standard	G4	G4	G4
Adjustable airflow	-	✓	✓
Control on mold curve	-	✓	✓
WiFi connection	-	✓	✓
Modbus	-	-	✓